



# CYBER SWITCHING®

## Dualcom S 460L5 (2 RU)

Part #2000021

The Dualcom S allows remote power management and represents a new approach to managing your system. Save energy by scheduling shutdown periods. Monitor current consumption to utilize valuable rack space efficiently.

### Technical Specifications

<b>Output</b>		<b>Outlet/Receptacle:</b>  <b>Input/Plug:</b> 
Output Voltage	120 VAC	
Output Connections	(4) NEMA L5-30R	
Output Current per Bank	30 A	
Output Current per Receptacle	30 A	
<b>Input</b>		
Input Voltage	120 VAC	
Input Frequency	60 Hz	
Input Connection Type	(2) NEMA L5-30P	
Cord Length	12 feet	
Input Current	60 A (2 x 30 A)	
Load Capacity	7,200 VA (2 x 3,600 VA)	
<b>Physical</b>		<b>Features:</b> <ul style="list-style-type: none"><li>• Events tracked in an event log, including change of outlet states, logins and logoffs, and user IP addresses.</li><li>• Receive event logs via SNMP, syslog, and e-mail automatically</li><li>• Assign descriptive names to each outlet</li><li>• Total system current displayed on seven-segment LED display</li><li>• Outlet memory restores outlet states in event of power outage</li><li>• Outlet states, under- and over-current warnings, and Virtual Circuit Breaker™ notices provided on front panel</li><li>• Supports temperature and humidity sensor for environmental monitoring</li></ul>
Net Weight	9.50 lbs.	
Maximum Height	3.50 inches	
Maximum Width	17.00 inches	
Maximum Depth	10.35 inches	
Shipping Weight	13.00 lbs.	
Shipping Height	6.00 inches	
Shipping Width	23.00 inches	
Shipping Depth	16.00 inches	
Color	Black	
<b>Environmental</b>		
Operating Environment	0 to 45° C	
Maximum Operating Relative Humidity	95%	
Storage	-25 to 85° C	
Regulatory Approval	cUL Listed, UL Listed, IEC 60950-1, FCC Class A	
<b>Warranty</b>		
Standard	2 years repair or replace	
Extended	Optional	
<b>Communication</b>		
Network Settings	10BaseT	
Serial Settings	RS-232 (Cisco DCE pin-out)	
<b>Accessories</b>		
Temperature/Humidity Sensor	P/N 2000023	

DERATE TO 80% FOR CONTINUOUS LOAD  
SUBJECT TO CHANGE WITHOUT NOTICE

Rev 2.1

