

CYBER SWITCHING®

Dualcom S 830i (1 RU)


Part #2000010

The Dualcom S allows remote power management and represents a new approach to managing your system. Save energy by scheduling shutdown periods. Monitor current consumption to utilize valuable rack space efficiently.

Technical Specifications

Output	
Output Voltage	120-240 VAC
Output Connections	(8) IEC 60320 C13
Output Current per Bank	20 A
Output Current per Receptacle	15 A
Input	
Input Voltage	120-240 VAC
Input Frequency	50/60 Hz
Input Connection Type	(2) IEC 60320 C20
Cord Length	8 feet
Input Current	30 A (2 x 15 A)
Load Capacity	7,200 VA (2 x 3,600 VA)
Physical	
Net Weight	5.50 lbs.
Maximum Height	1.75 inches
Maximum Width	17.00 inches
Maximum Depth	10.35 inches
Shipping Weight	9.00 lbs.
Shipping Height	6.00 inches
Shipping Width	23.00 inches
Shipping Depth	16.00 inches
Color	Black
Environmental	
Operating Environment	0 to 45° C
Maximum Operating Relative Humidity	95%
Storage	-25 to 85° C
Regulatory Approval	cUL Listed, UL Listed, IEC 60950-1, FCC Class A
Warranty	
Standard	2 years repair or replace
Extended	Optional
Communication	
Network Settings	10BaseT
Serial Settings	RS-232 (Cisco DCE pin-out)
Accessories	
Temperature/Humidity Sensor	P/N 2000023

Outlet/Receptacle:



Input/Plug:



Features:

- Events tracked in an event log, including change of outlet states, logins and logoffs, and user IP addresses.
- Receive event logs via SNMP, syslog, and e-mail automatically
- Assign descriptive names to each outlet
- Total system current displayed on seven-segment LED display
- Outlet memory restores outlet states in event of power outage
- Outlet states, under- and over-current warnings, and Virtual Circuit Breaker™ notices provided on front panel
- Supports temperature and humidity sensor for environmental monitoring

DERATE TO 80% FOR CONTINUOUS LOAD
SUBJECT TO CHANGE WITHOUT NOTICE

Rev 2.1

