

# CYBER SWITCHING®

## DUALCOM 1620V PLUS 520R 520P (0 RU)


Part # 1013017

The Dualcom PLUS allows remote power management and represents a new approach to managing your system. Save energy by scheduling shutdown periods. Monitor current consumption to utilize valuable rack space efficiently.


### Technical Specifications

<b>Output</b>	
Output Voltage	120 VAC
Output Connections	(16) NEMA 5-20R
Output Current per Bank	20 A
Output Current per Receptacle	20 A
<b>Input</b>	
Input Voltage	120 VAC
Input Frequency	60 Hz
Input Connection Type	(1) NEMA 5-20P
Cord Length	12 feet
Input Current	20 A
Load Capacity	2,400 VA
<b>Physical</b>	
Net Weight	10.10 lbs.
Maximum Height	65.00 inches
Maximum Width	1.75 inches
Maximum Depth	2.75 inches
Shipping Weight	13.10 lbs.
Shipping Height	72.00 inches
Shipping Width	7.50 inches
Shipping Depth	4.50 inches
Color	Black
<b>Environmental</b>	
Operating Environment	0 to 45° C
Maximum Operating Relative Humidity	95%
Storage	-25 to 85° C
Regulatory Approval (Pending)	cUL Listed, UL Listed, IEC 60950-1, FCC Class A
<b>Warranty</b>	
Standard	2 years repair or replace
Extended	Optional
<b>Communication</b>	
Network Settings	10BaseT
Serial Settings	RS-232 (Cisco DCE pin-out)

Outlet/Receptacle:



Input/Plug:



**Features:**

- Events tracked in an event log, including change of outlet states, logins and logoffs, and user IP addresses.
- Receive event logs via SNMP, syslog, and e-mail automatically
- Assign descriptive names to each outlet
- Total system current displayed on seven-segment LED display
- Outlet memory restores outlet states in event of power outage
- Outlet states, under- and over-current warnings, and Virtual Circuit Breaker™ notices provided on front panel

DERATE TO 80% FOR CONTINUOUS LOAD  
SUBJECT TO CHANGE WITHOUT NOTICE

Rev 2.1