



CYBER SWITCHING®

DUALCOM 1640V PLUS 520R 520P Dual Feed (0 RU)

Part # 1013021

The Dualcom PLUS allows remote power management and represents a new approach to managing your system. Save energy by scheduling shutdown periods. Monitor current consumption to utilize valuable rack space efficiently.

Technical Specifications

| | | |
|-------------------------------------|---|--|
| Output | | <p>Outlet/Receptacle:</p>  <p>Input/Plug:</p>  |
| Output Voltage | 120 VAC | |
| Output Connections | (16) NEMA 5-20R | |
| Output Current per Bank | 20 A | |
| Output Current per Receptacle | 20 A | |
| Input | | |
| Input Voltage | 120 VAC | |
| Input Frequency | 60 Hz | |
| Input Connection Type | (2) NEMA 5-20P | |
| Cord Length | 12 feet | |
| Input Current | 40 A (2 x 20 A) | |
| Load Capacity | 4,800 VA (2 x 2,400 VA) | |
| Physical | | <p>Features:</p> <ul style="list-style-type: none"> • Events tracked in an event log, including change of outlet states, logins and logoffs, and user IP addresses. • Receive event logs via SNMP, syslog, and e-mail automatically • Assign descriptive names to each outlet • Total system current displayed on seven-segment LED display • Outlet memory restores outlet states in event of power outage • Outlet states, under- and over-current warnings, and Virtual Circuit Breaker™ notices provided on front panel |
| Net Weight | 12.10 lbs. | |
| Maximum Height | 65.00 inches | |
| Maximum Width | 1.75 inches | |
| Maximum Depth | 2.75 inches | |
| Shipping Weight | 15.10 lbs. | |
| Shipping Height | 72.00 inches | |
| Shipping Width | 7.50 inches | |
| Shipping Depth | 4.50 inches | |
| Color | Black | |
| Environmental | | |
| Operating Environment | 0 to 45° C | |
| Maximum Operating Relative Humidity | 95% | |
| Storage | -25 to 85° C | |
| Regulatory Approval (Pending) | cUL Listed, UL Listed, IEC 60950-1, FCC Class A | |
| Warranty | | |
| Standard | 2 years repair or replace | |
| Extended | Optional | |
| Communication | | |
| Network Settings | 10BaseT | |
| Serial Settings | RS-232 (Cisco DCE pin-out) | |

DERATE TO 80% FOR CONTINUOUS LOAD
SUBJECT TO CHANGE WITHOUT NOTICE

Rev 2.1