

## Dualcom S Series Technical Specifications

MODEL#	Top Assembly	Input Voltage	Current Per Input Cord**	Input Connection
CS-DUAL-S-440i	2000020	120-240	40 A (20 x 20 A)	(2) IEC 60320 C20
CS-DUAL-S-460L5-30	2000021	120	60 A (2 x 30 A)	(2) NEMA L5-30P
CS-DUAL-S-460L6-30	2000013	208-240	60 A (2 x 30 A)	(2) NEMA L6-30P
CS-SINGLE-S-820	2000011	120	20A	(1) IEC 60320 C20
CS-DUAL-S-830i	2000010	120-240	30 A (2 x 15 A)	(2) IEC 60320 C20
CS-DUAL-S-S840	2000012	120	40 A (2 x 20 A)	(2) IEC 60320 C20
CS-DUAL-S-S840i	2000022	120-240	40 A (2 x 20 A)	(2) IEC 60320 C20

Current Per Outlet Receptacle**	Outlet Type	Dimensions
20	(4) EIC 60320 C19	17W x 1.35D x 1.75H
30	(4) NEMA L5-30R	17W x 10.35D x 3.50H
30	(4) NEMA L6-30R	17W x 10.35D x 3.50H
20	(8) NEMA 5-20R	17W x 10.35D x 1.75H
15	(8) IEC 60320 C13	17W x 10.35D x 1.75H
20	(8) NEMA 5-20R	17W x 10.35D x 1.75H
20	(8) IEC 60320 C19	17W x 10.35D x 1.75H

