



## Dualcom S SERIES TECHNICAL SPECIFICATIONS

Model No.	Input Voltage	Rated Current at Each Input	Input Connection	Output per Receptacle	Total Combined Output	Output Receptacle Type	Dimensions
<b>One (1) Input Connection, Eight (8) Output Receptacles</b>							
CS-SINGLE-S-820	120 V, 50/60 Hz	16 A	IEC 60320 C20	16 A	16 A	NEMA 5-20R	17" W x 10.35" D x 1.75" H
<b>Two (2) Input Connections, Four (4) Output Receptacles</b>							
CS-DUAL-S-440i	120-240 V 50/60 Hz	16 A (Total: 32 A)	IEC 60320 C20	16 A	2 banks: 16 A per bank	IEC 60320 C19	17" W x 10.35" D x 1.75" H
CS-DUAL-S-440L6-20	208-240 V 60 Hz	16 A (Total: 32 A)	NEMA L6-20P	16 A	2 banks: 16 A per bank	NEMA L6-20R	17" W x 10.35" D x 3.5" H
CS-DUAL-S-460L5-30	120 V, 60 Hz	24 A (Total: 48 A)	NEMA L5-30P	24 A	2 banks: 24 A per bank	NEMA L5-30R	17" W x 10.35" D x 3.5" H
CS-DUAL-S-460L6-30	208-240 V 60 Hz	24 A (Total: 48 A)	NEMA L6-30P	24 A	2 banks: 24 A per bank	NEMA L6-30R	17" W x 10.35" D x 3.5" H
<b>Two (2) Input Connections, Eight (8) Output Receptacles</b>							
CS-DUAL-S-830i	120-240 V 50/60 Hz	12 A (Total: 24 A)	IEC 60320 C20	12 A	24 A	IEC 60230 C13	17" W x 10.35" D x 1.75" H
CS-DUAL-S-840	120 V, 60 Hz	16 A (Total: 32 A)	IEC 60320 C20	16 A	16 A	NEMA 5-20R	17" W x 10.35" D x 1.75" H
CS-DUAL-S-840i	120-240 V 50/60 Hz	16 A (Total: 32 A)	IEC 60320 C20	16 A	32 A	IEC 60320 C19	17" W x 10.35" D x 1.75" H

Updated: October 6, 2022